

# POS Terminals

# EVO TP4

The EVO TP4 sets a whole new standard by offering enterprise-class build quality, P-CAP touchscreen technologies, and the latest in high-performance Intel® processors. Available with Celeron™, Pentium™, Core i3™, Core i5™, and Core i7™ processors, the EVO TP4 thrives in the most demanding environments. The EVO TP4 has an IP54 certified rating for both dust and splash resistance.



Shown with optional MSR



## Key Features



### Baytrail and Haswell Processors

Available with Intel Celeron, Pentium, Core i3,



### Touchscreen

15" (381mm) zero bezel, projected capacitive touchscreen technology



### Hard Drive

2.5" (64mm) 500GB HDD or 60-120GB SSD



### Built In Cable Management

Keeps cords out of sight



### EZHD Slot

Makes for quick HDD or SSD replacement



### IP54 Rating

Resistant to dust buildup and splashing water



### Aluminum Alloy Frame

Provides bump-free operation



### Optional Accessories

Optional integrated MSR, VFD customer display, 8.4" (213mm) rear LCD display, 15" (381mm) rear LCD display, or Biometric Reader display, or Biometric reader.

MODELS	EVO-TP4D-F	EVO-TP4D-G	EVO-TP4D-H	EVO-TP4D-J	EVO-TP4D-K	EVO-TP4D-L
Processor	Intel® Celeron J1900 2.4GHz Quad Core*	Intel® Celeron G1820 2.7GHz Dual Core*	Intel® Pentium G3420 3.2GHz Dual Core*	Intel® Core i3-4330 3.5GHz Dual Core*	Intel® Core i5-4570S 3.6GHz Quad Core*	Intel® Core i7-4770S 3.9GHz Quad Core*
Chip Set	Processor Integrated	Intel Lynx Point PCH H81				
System Memory	1 x DDR3L 4GB to 8GB	1 x DDR3 DIMM 4GB to 8GB				
Hard Drive	500GB HDD or 60-500GB SSD					
Graphic Memory	Intel Gen7 up to 854MHz	Intel® HD Graphic DX11.1				
GigaLAN (10/100/1000)	1 x RJ45					
Weight (w/base)	15 lbs (6.8kg)	15.4 lbs (7kg)				
Electrical	65W/19V	120W/19V				

PORTS	EVO-TP4D-F	EVO-TP4D-G	EVO-TP4D-H	EVO-TP4D-J	EVO-TP4D-K	EVO-TP4D-L
Parallel	1					
USB	5 x USB Type A (USB 3.0 / 2.0 x1, USB 2.0 x4)	6 x USB Type A (USB 3.0 / 2.0 x2, USB 2.0 x4)				
Serial	3 x RJ45 COM3 with 5V/12V	3 x RJ45 COM3 with 5V/12V, 1 DB9				
VGA	1					
Cash Drawer Port	1					
Speakers	2					

PHYSICAL	
Housing	Die Cast Aluminum
Dimensions (w/base) (WxDxH)	14.21" x 9.76" x 13.27" (361mm x 248mm x 337mm)
VESA Wall Mountable	3.9" x 3.9" (100mm x 100mm)
Tilt Angle	0° – 90°
Housing Color	Black
Bezel	TruFlat Zero Bezel
LCD Display	15" (381mm) LED LCD
Touch Technology	Projected Capacitive (P-CAP)

ENVIRONMENTAL	
Ingress Protection	IP54-Resistant to dust buildup and splashing water
Operating Temperature	32°F to 95°F (0°C to 35°C)
Humidity	20% to 80% non-condensing
Warranty	3-year warranty with free **2-day Advance Exchange Service
Certifications	FCC, Class A, CE, LVD, RoHs, NOM
Supported OS	Win 7, Win 8, Win 10, Available with no O/S

WARRANTY EXTENSION AND UPGRADES	
ZWE-TPC	2-Year Warranty Extension
ZOE-TPC3	**3-Year Overnight Exchange
ZOE-TPC5	**5-Year Overnight Exchange

OPTIONAL ACCESSORIES	
EVO-MR4	3 Track Magnetic Stripe Reader with USB interface
EVO-BR4	Integrated U.are.U 4500 BIO Reader
EVO-RD4-VFD	Integrated 2x20 VFD Customer Display
EVO-RD4-LCD8	Integrated Rear Display, 8.4" (213mm) LCD w/VGA Cable & Mount
EVO-RD4-LCD15	Integrated Rear Display, 15" (381mm) LCD w/VGA Cable and Mount
EVO-XZ4-M100	Universal VESA Mount for All Terminals and Touch Monitors

\*Shipped product may include an equivalent or faster processor. Processor speeds based on Passmark® benchmark scores. Speeds shown are maximum burst speed.

\*\*Available in USA and Canada.