

# The versatile, reliable impact printer that makes a great impact on your business.

- Fast, consistent impact printing.
- Snap-in/snap-out, user-friendly ribbon cassette features Oki<sup>®</sup> impact technology.
- Choose from four different Series 150 models.
- Ready to configure easily into whatever system you're using.
- Space-saving footprint.



Meet the Ithaca® Series 150 impact printer. Leading companies in the POS and hospitality industries trust the Ithaca brand for fast, reliable printers that last. Our 150 is a compact, economical printer with excellent reliability and an industry-leading warranty. It prints at speeds of 9.5 lines per second, and has the flexibility of receipt, journal and validation capabilities. Our 150 also utilizes Oki® technology, known worldwide for quality, reliability and a snap-in/ snap-out, user-friendly ribbon cassette. We have four different 150 models to choose from, each delivering high performance at an extremely low total cost of ownership, together with a 2-year warranty offering extended maintenance options. And, of course, the Series 150 is backed by our solid reputation for quality and reliability.

## **OUR MODELS**

- 151 Receipt (When ordered with Auto-Cut option, single-piece spill-resistant cover is standard.)
- 152 Receipt/Journal
- 153 Receipt/Journal/15-line Validation
- 154 Receipt/15-line Validation

## **OUR PRINTING CHARACTERISTICS**

Pitch Maximum Style **Print Speed** (char./in.) (char./line) (lines/sec.) 9.5@10 char./line Condensed 17.1 48 48 5.9@40 char./line

# **OUR INTERFACE OPTIONS**

RS232C: **Bi-Directional Serial (9-Pin)** IEEE1284: Bi-Directional Parallel (25-Pin) Universal Serial Bus (USB)

## **OUR PRINTER DRIVERS**

Windows<sup>™</sup> 95/98/2000/Me/XP, NT 4.0, OPOS

# **OUR OPTIONS**

- Journal Lock
- Display Pass-Thru (Serial Only)
- Auto-Cutter-Partial Cut leaves a 1 mm (.04 in.) tab in center of receipt.
- Light Gray or Black Cabinetry

# **OUR POWER REQUIREMENTS**

Internal Universal AC Power: 90 VAC to 264 VAC (Self-Ranging), 47 to 63 Hz

## **OUR RELIABILITY**

Printer in full operation (using all available features)\* MCBF: 4,000,000 to 5,000,000 Print Lines (Depending on Model) MTBF: 22,000 to 30,000 Hours (Depending on Model) Printhead: 200,000,000 Characters Auto-Cutter: 1,000,000 Cuts Made to Order. Built to Last.®

\* Reliability data is based on our standard test conditions simulating a normal retail operating environment.

## **OUR ENVIRONMENTAL SPECS**

**Operating Temperature:** 0 to +50 degrees C (32 to +122 degrees F) **Operating Humidity:** 10 to 90% RH non-condensing

## **OUR REGULATORY COMPLIANCE**

FCC Class A UL 1950

# VDE 950 **OUR SUPPLIES AND SERVICE**

CSA 950

CE Mark

We offer convenient one-stop shopping for all your printer needs - paper, spare parts, manuals, printer servicing/refurbishment and more. For more information, call us at 1.877.7ithaca or visit our Web site at www.ithacaprinters.com.

## **OUR FEATURES AND BENEFITS**

- Print Speed: 9.5 lps. (340 cps.)—On Standard Test Receipt
- Standard Warranty: Two Years (Extended Maintenance Plan Available) •
- Cash Drawer Drivers: Dual with Status (RJ11)
- Print Zone Widths: 61 mm (2.4 in.) or 72 mm (2.8 in.) •
- Data Buffer: Up to 6K Configurable
- CPI: 4, 6, 8.5, 10, 12, 15, 17.1, 20, 24
- APA Bit Map Graphics
- Portrait or Landscape Printing
- Simple Loading of Receipt Paper
- Available Emulations: Ithaca/IBM (PcOS®), Epson\* ESC/POS®, Microline, Star •
- 67 Language Code Pages
- Self Diagnostics •
- Concealed Cable Entry •
- Bar Codes: Code 39, Code 93, Interleaved 2 of 5, UPC-A and UPC-E, EAN8 and EAN13, Code 128
- Interface Parameters: Software Configurable via Buttons or Interface Port
- \* Licensed Command Firmware available as an option.

# **OUR MEDIA**

# Paper Roll (One-Ply):

- Width: 82.5 mm (3.25 in.) or optional 76 mm (3 in.)
- Diameter: 89 mm (3.5 in.)
- Length Per Roll: 73.1 m (240 ft.)
- One-Ply Maximum Thickness: .11 mm (.0045 in.)

# Paper Roll (Two-Ply):

- Width: 82.5 mm (3.25 in.)
- Diameter: 89 mm (3.5 in.)
- Length Per Roll: 38.1 m (125 ft.)
- Maximum Thickness Per Ply: .09 mm (.0035 in.) •
- Paper Roll (Three-Ply, not for use with Model 151 with Auto-Cut):

# Width: 82.5 mm (3.25 in.)

- Diameter: 89 mm (3.5 in.) •
- Length Per Roll: 26 m (85 ft.) •
- Maximum Thickness Per Ply: .25 mm (.01 in.)
- **Ribbons: 3-4.5 Million Character Life**
- Ithaca or Genuine Oki Snap-on Ribbon Cassette (Black or Purple)

## **OUR PHYSICAL CHARACTERISTICS**

**Dimensions:** 171.45 mm W x 287 mm D x 142 mm H (6.75 in. W x 11.3 in. D x 5.6 in. H) Weight: 2.95 kg (6.5 lbs.) Shipping Weight: 4.32 kg (9.5 lbs.)

WHO WE ARE

## TransAct Technologies, Inc. (NASDAQ: TACT) designs, develops, manufactures and markets transaction-based printers under the Ithaca® and Magnetec® brand names. In addition, the company markets related consumables, spare parts and service. The company's printers are used worldwide to provide receipts, tickets, coupons, register journals and other documents. The company focuses on the following vertical markets: point-of-sale (POS), and gaming and lottery. All of TransAct's products are manufactured in ISO9001-certified facilities.

## WHERE TO REACH US

TransAct Technologies, Inc. Ithaca Facility 20 Bomax Drive Ithaca, New York 14850 1.877.7ithaca (1.877.748.4222) Fax: 607.257.3868 www.ithacaprinters.com

TransAct Technologies, Ltd. 7 Wood View **Broomhouse Lane Industrial Estate** Edlington, Doncaster DN12 1EQ **United Kingdom** Phone: ++44 (0) 1709 772500 Fax: ++44 (0) 1709 772505



© 2003 TransAct Technologies, Inc. Contents of this publication may be changed without notice and shall not be regarded as a warranty. The Ithaca name and logo, Made to Order. Built to Last., and PcOS are registered trademarks of TransAct Technologies. Windows is a registered trademark of Microsoft Corporation. IBM is a registered trademark of International Business Machines Corporation. ESC/POS is a trademark of Seiko Epson Corporation. Star is a registered trademark of Star Micronics Corporation. Oki is a registered trademark of Okidata Corporation. All rights reserved.