



## KEY FEATURES

- Intel Celeron® M 1.5GHZ w/ 1MB cache
- Microsoft® Windows XP or WEPOS
- 160GB SATA HDD
- 1GB DDR2 Memory
- 4 DB9 Serial Ports
- 6 USB Ports (2 on side of display)
- 15" touch screen display
- Private label front bezel logo (option)

# KS6600 Series

## Posiflex KS6600 Series

Posiflex's KS6600 Series features a VAR-inspired improved base design for easy installation and service, including a front-panel pull-out SATA hard drive. We've also added many other installation-friendly features including DB9 Serial Ports and additional USB Ports. The KS6600 Series offers the industry's most powerful fan-free terminal with an Intel Celeron® M 1.5GHz CPU with 1MB of Level 2 cache. Optimized for true "Plug-n-Play" functionality with applications running Microsoft WEPOS (windows Embedded Point-of-Service) software, the KS6600 comes standard for your desktop or with an optional wall mount for the 15" display.

**For more information call 888.968.1668 today!**

# Specifications

Function	KS6615
Processor	Intel Celeron® M - 1.5GHz [1MB L2 cache, PGA]
System Memory	DDR2 533 MHz SODIMM x 1, max 1GB
Default Memory	1GB DDR2
Video Memory	Dynamic video memory up to 128MB [shared]
Power Supply	12V DC power adaptor, 80W
Housing	Aluminum Alloy
Speaker	Built-in
OS Support	Microsoft® Win XP Pro / WEPOS / POS Ready
Safety Certifications	FCC-A, CE-A, RoHS
Display	
LCD	15" LCD, 250nits, 1024 x 768 [XGA]
Touch Sensor	15" Resistive or Infrared
Brightness Control	Hardware push button switch control or software control
Tilt Adjustment	From 15° to 70°
Expansion	
Storage Device	2.5" 160GB SATA HDD
Mounting Option	Desktop or wallmount
Connectivity	
Audio Port	2 Watt audio amplifier with internal speaker Mic. In/line out ports
LAN Port	1 x 10/100/1000 Base T Ethernet
Parallel Port	1 x SPP / EPP / ECP
Serial Port	4 x DB9, each with +5V power supply capability
UPS Port	1 x, battery health auto-check
Standard USB Port	6 x, USB 2.0, 4 in I/O panel, 2 in side cover
Proprietary USB Port	1 x, for side mount option liek SD-404
VGA Port	1 x, sub D 3 x 5 pins, RBG analog
CR Port	1 x
Environment	
Operation Condition	28% RH ~ 80%RH, non-condensing max, wet bulb 28°C [78.7°F]
Storage Condition	20°C ~ +60°C [4°F ~ +140°F] without UPS battery, -20°C ~ +40°C [-4°F ~ +104°F] with UPS battery, 10%RH ~ +80%RH, non-condensing max, wet bulb 28.9°C [84.0°F]
Options	
2nd HDD	Yes
2nd LCD Display	LM6101 Series
Customer Pole Display	PD2604: 11mm, 2x20 VFD display, 5x7 dot matrix, RS232 interface PD2602: 9mm, 2x20 VDF display, 5x7 dot matrix, RS232 or USB interface PD305: 9mm, 2x20 LCD display, 5x7 dot matrix, RS232 or USB interface
SD-404 Magnetic Stripe Reader	Optional 2-track or 3-track MSR with/without Finger Print Sensor
UPS Battery	2.3 Ahr / 12V, in base stand
PORT CONFIGURATIONS	

OPTIONS
<p>Leverage digital signage opportunities w/the LM6000 Secondary Display</p>
<p>PD305B Customer Display</p>
<p>PD2602 Customer Pole Displays</p>
<p>MSR w/ DigitalPersona Fingerprint Biometrics</p>

## About Posiflex

Posiflex has four primary objectives - provide revolutionary technology, reliable quality, reasonable pricing and recognized service. As a 25 year design and manufacturer of Point-of-Service (POS) and industrial touch terminals, Posiflex has over 30 patents awarded for innovative design as a POS pioneer, and leader. In partnership with software application companies, Posiflex's products are sold worldwide through VARS and distributors to various vertical industries. Posiflex's comprehensive suite comprises of a wide range of peripherals, terminals ranging from small footprint electronic cash register replacements, to POS terminals, to robust back office file servers in our two ISO 9001/9002/ 14001 certified facilities.

**POSIFLEX™**

Be the Pioneer, Be the Leader

30689 Huntwood Avenue

Hayward, CA 94544

Toll-free: 888.968.1668

Phone: 510.429.7097

Fax: 510.475.0982

E-mail: sales@posiflexusa.com