



M150 High Brightness LCD Touch Monitor



DURABLE

STURDY

ADJUSTABLE

ACCURATE

Product Highlights

- 500:1 Contrast Ratio
- 500 Nit Brightness
- Peripheral Attachment System
- Locking adjustment angle
- Locking user controls
- Warranty: 3-year LCD, 5-year touch screen and components

Enhanced Video Performance

The MicroTouch™ M150HB 15" LCD Touch Monitor delivers enhanced display performance in a built-for-touch form factor. With 500 Nit brightness and a 500:1 contrast ratio, this touch screen monitor is ideal for a multitude of applications, and excels in high ambient light environments where standard display panels could “wash-out” or look dim. The enhanced brightness and contrast also help produce more vivid, distinct colors – giving graphics and color intensive applications ideal visual appeal.

The M150HB monitor offers maximum touch stability and installation flexibility with the added benefit of enhanced LCD display performance. Potential applications for the M150HB include POS stations situated near windows, shaded outdoor applications in retail and hospitality, and anywhere high ambient light conditions could diminish perceived display quality.*

Making the Difference

Available with USB connectivity, the MicroTouch™ M150HB LCD monitor is offered with MicroTouch™ ClearTek™ II capacitive touch technology. ClearTek™ II touch screens, combined with the solid foundation of MicroTouch™ EX II electronics and robust MicroTouch™ software offer high endurance solutions for a multitude of touch applications where exceptional performance, vibrant optics and environmental robustness is mission critical, 24/7.

*The M150HB is not intended for use or readability in direct sunlight.

M150HB LCD Touch Monitor

Functional Features

15" LCD

LCD Technology	TFT, Active Matrix
Display Colors	16M
Pixel Pitch	.297 mm
Brightness without touch screen	550 cd/m2 typical
Brightness with touch screen (max.) ¹	500 cd/m2 typical
Contrast Ratio	500:1
Response Time	12 ms typical
Viewing Angle (from center)	Horizontal: 140 degrees total typical Vertical: 120 degrees total typical
Front Panel Buttons	Menu, Select, Adjust, Power
On Screen Display Controls	Brightness, Contrast, Horizontal/Vertical Position, Clock, Phase, Auto Phase, Color
Maximum Resolution	1024 x 768
Operating Environment	Operating Temperature: 0 to 40 degrees C Relative Humidity, Non-condensing 85%
Storage Environment	-20 to +60 degrees C



Key hole pattern in base allows bolt-down mounting.

Physical Features

Physical Dimensions (WxHxD) (Depth includes base)	408 x 398.3 x 258.7 mm 16.1 x 15.7 x 10.2 inches
Display Area (WxH)	304.1 x 228.1 mm, 12 x 9 inches
Video Cable Connector	15-pin D-sub
Power Supply	12V DC Power Supply
Power Savings ²	DPMS, VESA Compliant
Power Consumption	<35W, Normal Operation
Backlight Life	50,000 hrs. typical
Weight (Net)	7.4 kg/16.3 lbs.
Agency Approvals	FCC B, CE, UL/cUL, C-Tick, VCCI, CCC
Mounting Options	VESA mounting compatible, 75mm
Multimedia	Stereo Speakers, Microphone, Volume, Line-in
Color Option	Black
Controller Option	USB
Warranty	3 Years FPD, 5 Years Touch Screen and Components
Part Numbers	11-81376-225 (Black, Capacitive, USB)



Peripheral Attachment System allows use of multiple peripheral devices.

(1) Brightness measured using MicroTouch ClearTek™ II Capacitive

(2) DPMS: Display power management signaling for reduced power consumption during non-use.



3M Touch Systems, Inc. 3M Optical Systems Division

300 Griffin Brook Park Drive
Methuen, MA 01844
U.S.A.
1-866-407-6666
www.3Mtouch.com

Worldwide Manufacturing Plants

Methuen, Massachusetts
Milwaukee, Wisconsin
Vancouver, BC Canada

For more information
on 3M touch products,
visit 3Mtouch.com or
call toll-free 1-866-407-6666

NOTICE: Given the variety of factors that can affect the use and performance of a 3M Touch Systems Product (the "Product"), including that solid state equipment has operation characteristics different from electro mechanical equipment, some of which factors are uniquely within User's knowledge and control, it is essential that User evaluate the 3M Touch Systems Product and software to determine whether it is suitable for User's particular purpose and suitable for User's method of application. 3M Touch Systems' statements, engineering/technical information, and recommendations are provided for User's convenience, but their accuracy or completeness is not warranted. 3M Touch Systems products and software are not specifically designed for use in medical devices as defined by United States federal law. 3M Touch Systems products and software should not be used in such applications without 3M Touch Systems' express written consent. User should contact its sales representative if User's opportunity involves a medical device application.

IMPORTANT NOTICE TO PURCHASER: Specifications are subject to change without notice. These 3M Touch Systems' Products and software are warranted to meet their published specifications from the date of shipment and for the period stated in the specification. **3M Touch Systems makes no additional warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose.** User is responsible for determining whether the 3M Touch Systems Products and software are fit for User's particular purpose and suitable for its method of production, including intellectual property liability for User's application. If the Product, software or software media is proven not to have met 3M Touch Systems' warranty, then 3M Touch Systems' sole obligation and User's and Purchaser's exclusive remedy, will be, at 3M Touch Systems' option, to repair or replace that Product quantity or software mediator to refund its purchase price. 3M Touch Systems has no obligation under 3M Touch Systems' warranty for any Product, software or software media that has been modified or damaged through misuse, accident, neglect, or subsequent manufacturing operations or assemblies by anyone other than 3M Touch Systems. **3M Touch Systems shall not be liable in any action against it in any way related to the Products or software for any loss or damages, whether non-specified direct, indirect, special, incidental or consequential (including downtime, loss of profits or goodwill) regardless of the legal theory asserted.** (7/02)