

Magellan® 8200Ω

With OmegaTek™ Productivity Technology



Features:

- OmegaTek™ Productivity Technology
- Enhanced All-Weighs™ Platter
- Aggressive & ergonomic 5-sided scanning
- Multiple interface solution supports all popular host interfaces
- FirstStrike™ Advanced Decoding Software
- Flash memory for easy, low cost upgrades
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Host Download
- Diagnostic Reporting
- Optional Productivity Index Reporting™ (PIR)
- RSS Decoding
- Optional EAS functionality
- Sunrise 2005 Compliant



"Nothing Beats a Magellan®"

Mechanical

Length & Weight

Model	Scanner/Scale	Length	Weight
8200Ω	short scanner	13.9" / 35.3 cm	13.0 lbs. / 5.9 kg
8201Ω	medium scanner	15.7" / 39.9 cm	15.0 lbs. / 6.9 kg
8202Ω	med. scanner/scale	15.7" / 39.9 cm	18.0 lbs. / 8.2 kg
8203Ω	long scanner	20.0" / 50.8 cm	15.0 lbs. / 6.9 kg
8204Ω	long scanner/scale	20.0" / 50.8 cm	20.0 lbs. / 9.1 kg

Width: 11.5" / 29.2 cm

Depth (below counter): 4.0" / 10.0 cm

Height (above counter): 51" / 131 cm

Scale Capacities

Capacity: 30.0 lbs. / 999 kg or 15 kg (host dependent)

Minimum increment: 0.01 lb. / 0.005 kg

Vibration immunity: 4 programmable filter settings

Maximum static weight: 150 lbs. / 68 kg

Adjustments required: Calibration only

Optical

Scan lines: 48

Motor speed: 6,000 rpm

Scan rate: 4,800 lines/sec.

Scan zone: 360°

Sides read: 5

Read height: 6.0" / 15.2 cm

Environmental

Temperature Rating:

Operating: 50° to 104° F / 10° to 40° C

Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

Decoding Capability

The Magellan® 8200Ω autodiscriminates between the following supported symbologies:

- UPC Versions A & E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & CI28)
- Reduced Space Symbology (RSS-I4, expanded & stacked)
- EAN 8, I3
- JAN 8, I3
- EAN/JAN two label
- UCC/EAN I28
- Code 39 (with full ASCII)
- Code I28
- Code 93
- Interleaved 2 of 5
- Italian Pharmacode
- Codabar/NW7
- MSI/Plessey

Electrical

AC Power requirements:

100-250 VAC, 50-60 Hz

11 Watts (nominal)

14 Watts (maximum)

4 Watts (sleep mode)

Communications

Host: All Magellan® 8200Ω models support IBM 46XX, RS-232, and IBM USB. There is an optional Keyboard Wedge for the scanner-only version.

Other:

Powered RS-232 auxiliary port

Scale host port

Remote scale display port

EAS interlock port

Safety & Regulatory

Electrical: IRAM (Argentina), AS/NZS 60950 (Australia); CSA-C22.2 No. 60950 (Canada); EN60 950 (TÜV Europe); PSE Mark (Japan); UL 60950 (USA)

Emissions: FCC part 15, Class B (USA); AS/NZS 3548 (Australia/New Zealand); EN 55022-B (Europe); CISPR 22-B, VCCI-B (Japan)

Laser safety: Class IIa Laser Product

(CAUTION: Laser Light – do not stare into beam); IEC 825 Class 1, EN60 825 Class (Europe)



Weights and Measures: Argentina; Australia; Brazil; Canada; 90/384/EEC (Europe); Mexico; New Zealand; USA (NIST Handbook 44)

Contact your PSC representative for certification schedule and additional listings.

Other

EAS compatibility: Integrated EAS hardware will work with Counterpoint IV, V, VI, and VII models available from Checkpoint® Systems.

Good Read acknowledgement with Sensormatic®.

PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140



© 2005 PSC, Inc. All rights reserved. • PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. • PSC, Magellan, SurroundScan, and the PSC logo are registered trademarks of PSC Inc. OmegaTek, 3D Scanning, All Weighs, First Strike, Productivity Index Reporting (PIR), and Cashier Training are trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com • Product specifications are subject to change without notice.

R40-0120-US B 0505

