

# DROP-IN



## 3 inch Impact Dot POS Printer SRP-275II



BIXOLON SRP-275II is more powerful and enhanced performance impact dot POS printer to address customers' needs in restaurant, hospitality and retail industries. The fastest speed in its class(5.1 lps) allows kitchen orders to print faster than ever with two color, black and red printing to highlight special offers and print logos. Compact size with embedded power supply maximizes the efficiency of working environment. Eco-friendly design of the lowest standby power and various international standards provide reliability of the SRP-275II to the users.

BR-SRP-275II-EN-MAR14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

## BIXOLON®

www.bixolon.com



### BIXOLON Co., Ltd.

7~8F, (Sampyeong-dong), 20, Pangyoeyeok-ro241beon-gil,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

### PRINT CHARACTERISTICS

**Print Method** : 9 Pin / Serial Dot Matrix

**Print Speed** : 5.1 lps

**Print Resolution** : 80 dpi (horizontal) / 144 dpi (vertical)

**Print Width** : Up to 63.5 mm

**Sensor** : Paper End, Paper Near End, Wall Mounting Paper Near End,  
Rear Cover Open, Black Mark

### MEDIA CHARACTERISTICS

**Media Type** : Receipt

**Media Width** : 76.5 mm

**Media Roll Diameter** : Up to 83 mm

**Media Roll Diameter** : 0.06 ~ 0.085 mm

**Supply Method** : Easy Paper Loading

### PHYSICAL CHARACTERISTICS

**Dimensions (W x L x H)** : 160 x 239 x 157 mm  
(6.29 x 9.40 x 6.18 inch)

**Weight** : A: 2.4 kg (5.29 lbs.) / C: 2.5 kg (5.51 lbs.)

**Power** : EnergyStar Certified,  
External Power Adaptor 100-240V AV, 50/60Hz

**Drawer Port** : 2 ports (via y-type adaptor)

### PERFORMANCE CHARACTERISTICS

**Memory** : 64 Mbit SDRAM, 16 Mbit FlashROM

**NV Image Memory** : 256 Kbytes

**Receive Buffer** : 64 Kbytes

**User Define Buffer** : 64 Kbytes

**Interface** : USB V2.0 HS, Serial, Parallel, Ethernet

### ENVIRONMENT CHARACTERISTICS

**Temperature** : Operating: 0 ~ 40°C (32 ~ 104°F)  
Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity** : Operating: 10 ~ 80% RH  
Storage: 10 ~ 90% RH

### RELIABILITY

**Printer Unit (MCBF)** : 18 Million Lines

**TPH** : 300 Million Dots/Wire

**Auto Cutter** : 1.5 Million Cuts

### SOFTWARE

**Emulation** : BXL / POS

**Driver** : Windows Driver, OPOS Driver, JPOS Driver, Linux CUPS Driver,  
Mac Driver, Virtual COM USB/Ethernet Driver, Utility Program

**SDK** : iOS SDK, Android SDK

### FONTS / GRAPHICS / SYMBOLOGIES

**Character Size** : Font A: 9 x 9 Font B: 7 x 9 / KOR: 17 x 9 CHN: 16 x 16

**Characters Per Line** : Font A: 35 Font B: 40 / KOR: 20 CHN: 22

**Character Sets** : Alphanumeric: 95

Extended Graphics: 128 x 27 page

International: 48

**Graphics** : Supporting user-defined fonts, graphics, formats, and logos

### ACCESSORIES

**Optional** : Wall Mount (RWM-350)

Splash Proof Cover (RSC-275)

B-melodist (RMB-100)

### BIXOLON America Inc.

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

### BIXOLON Europe GmbH

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de