



With a sleek yet robust design, the EVO TP6 is the perfect enterprise-grade POS solution. The EVO TP6 features a 15" TruFlat projected capacitive touchscreen, a range of Intel CPUs, cable free accessories and a versatile dual hinge design.



Resilient Touch Display

The EVO TP6 features a 15" LCD screen with TruFlat projected capacitive (PCAP) multi-touch technology built to take the rigors of heavy use.



Versatile Platform

A dual hinge design allows for efficient shipping and almost unlimited tilt angles. Built-in VESA mounting extends the versatility of the platform to any wall mount installation.



Fan-less Design

A fan-less design provides a sleek, clean look and silent operation. No vent openings mean better protection from dust and water reaching an IP54 ingress protection rating.



Efficient High Performance CPUs

With support for Intel CPUs ranging from the efficient J1900 to the powerful Core i5, the EVO TP6 is sure to fit any application



| MODEL | EVO-TP6D-F | EVO-TP6D-P | EVO-TP6D-3 | EVO-TP6D-5 |
|----------------|---------------------------------------------------------------|-------------------------------------------------------------------------------|---------------------|---------------------|
| Processor | Intel Celeron J1900 | Intel Pentium 4405U | Intel Core i3-6100U | Intel Core i5-6200U |
| Bezel | TruFlat Zero Bezel | | | |
| Chip Set | Processor Integrated | | | |
| System Memory | 1 x DDR3L SO-DIMM 8GB | | | |
| Hard Drive | 2.5" 64-500GB SSD or 2.5" 500GB HDD | | | |
| LCD Display | 15" (381mm) TFT LCD | | | |
| Resolution | 1024x768 | | | |
| Touch | PCAP, 10 Point Multi-Touch | | | |
| Brightness | 300 nits | 350 nits | | |
| Graphic Engine | Intel HD Graphics DX11 and OCL1.1 | Intel HD Graphics DX12 and OCL4.2 | | |
| Electrical | 65W/19V | 90W/19V | | |
| Supported OS | Win 7 Pro (x32/x64), POSReady 7(x32/x64), Win 10 IoT(x32/x64) | Win 8.1 Embedded (x64), Win 8.1 Pro (x64), Win 10 IoT (x64), Win 10 Pro (x64) | | |

| PORTS | EVO-TP6D-F | EVO-TP6D-P | EVO-TP6D-3 | EVO-TP6D-5 |
|------------------|-------------------------------|----------------------------------|------------|------------|
| USB | 4 x USB 2.0 / 1 x USB 3.0 | 2 x USB 2.0 Type A / 4 x USB 3.0 | | |
| Serial | 3 x RJ45 with 0V/5V/12V power | | | |
| LAN | 1 x RJ45 | | | |
| Cash Drawer Port | 1 x RJ11 (12V/24V) | | | |
| VGA | 1 x DB15 | | | |

| PHYSICAL | |
|--------------------|--------------------------------------------|
| Housing | Die Cast Aluminum |
| Weight | 13.2lbs (6Kg) |
| Dimensions (WxDxH) | 14.2" x 8" x 10.9" (360mm x 203mm x 277mm) |
| Tilt | Dual Hinge |
| Housing Color | Black |
| Wall Mount | 100mm VESA (75mm or 100mm with base) |

| ENVIRONMENTAL | |
|-----------------------|-----------------------------|
| Operating Temperature | 32°F - 95°F (0°C - 35°C) |
| Humidity | 20% - 80% RH non-condensing |
| Certifications | FCC Class B, CE, LVD, |
| IP Rating | IP54 (Front) |

| OPTIONAL ACCESSORIES | |
|---------------------------|--------------|
| 3 Track MSR | EVO-MR6 |
| Fingerprint Reader | EVO-BR6 |
| 2 Line Customer Display | EVO-RD6-LCM |
| 8.4" LCD Customer Display | EVO-RD6-LCD8 |

| WARRANTY EXTENSION AND UPGRADES | |
|---------------------------------|-----------------------------------------------------------|
| ZWE-TPC | 2-Year Warranty Extension |
| ZOE-TPC3 | *Next Business Day Protection |
| ZOE-TPC5 | *2-Year Warranty Extension + Next Business Day Protection |

*Available in USA and Canada.