



P310i

PERFORMANCE



Single-Sided Color Card Printer Optimised for Fast Color Printing

The Zebra P310i is an easy to use, reliable, single-sided card printer with convenient features to produce superior quality printing at an affordable price.

Use the P310i card printer to print:

- » Employee ID cards
- » Time and Attendance cards
- » Student ID's and Facilities Access Control cards
- » Club Membership and Loyalty cards

Zebra P310i Advantages

Advanced Color Printing: Enhanced color-processing firmware and new richer color formulation

Reliable Operation: Based on the highly reliable, field-proven P310 print engine

i Series Intelligent Printing System: Enhanced i Series functionality makes high image quality card printing a simple function for all users. The system features:

- » Advanced RFID Technology
- » Automatic Driver Configuration
- » Intelligent Color Optimization
- » Ribbon Image Counter & Ribbon Low Notification
- » Enhanced Ribbon Formulation

Basic Specifications:

- » 25 Seconds/Card Print Speed
- » Full Color Single-Sided Card Printing
- » Parallel or USB Interface
- » 75 Card Capacity Feeder
- » i Series Printers require the use of TrueColours™ i Series ribbons for full color printing

P310i Card Printer

*i*series



Card
Printer
Solutions

P310i

Card Printer Product Specifications



General Specifications

- » High speed printing
- » 144 cards/hour for color, single sided (YMCKO)
- » 900 cards/hour for resin black (K)
- » 2MB image memory standard
- » Windows® drivers for 98, ME, NT, 2000 and XP
- » Bi-directional driver communication
- » One year printer warranty
- » One year (unlimited passes) printhead warranty

Color Printing

- » Color dye sublimation or monochrome thermal transfer printing
- » 25 seconds per card full color single sided (YMCKO)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Fonts

- » True Type fonts via Windows driver

Card Specifications

- » Types: PVC, PVC Composite
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card-ISO 7816-2
- » Card thickness: 10 mil (.25mm) to 60 mil (1.524mm)
- » Card feeder capacity: 75 cards (30 mil)
- » Card output hopper capacity: 75 cards (30 mil)

Ribbon Specifications

- » i Series Printers require the use of i Series ribbons for full color printing
- » Monochrome: 1500 & 1000 cards/roll
- » Monochrome colors: black, red, blue, green, silver, gold, white and scratch-off grey
- » YMCKO: 200 & 330 cards/roll
- » KdO: 500 cards/roll
- » KrO: 500 cards/roll
- » Overlay varnishes: Clear and Hologram: 350 cards/roll



Communications Interface

- » Centronics Parallel (parallel cable included)
- » USB Option

Mechanical

- » Width: 12.4in (315mm)
- » Depth: 7.75in (198mm)
- » Height: 8.7in (220mm)
- » Weight: 13.4lbs (6.1kg)

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » FCC Class B, CE, UL and CUL approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » USB Interface
- » Smart card contact station (30 mil cards only)
- » Magnetic encoder (30 mil cards only)
- » Cleaning supplies
- » Service manual

<http://cards.zebra.com>

*Optimized for use with Zebra media.



Zebra Technologies Corporation



An ISO 9001 registered company ©2004 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof. **Part No. P310-03/04**

North America

Zebra Technologies Corporation
Card Imaging Division
1001 Flynn Road
Camarillo, CA 93012-8706
USA
Telephone: +1 805 579 1800
Fax: +1 805 579 1808
Toll free in US: 800 452 4056
e-mail: cards@zebra.com

Europe, Middle East, Africa

Zebra Technologies Corporation
Card Imaging Division
The Valley Centre, Gordon Road
High Wycombe
Buckinghamshire HP13 6EQ, UK
Telephone: +44 870 241 1527
Fax: +44 870 241 0765
e-mail: eurosales@zebra.com

Asia Pacific

Zebra Technologies Corporation
Card Imaging Division
1 Sims Lane #06-11
387355 Singapore
Telephone: +65 6858 0722
Fax: +65 6885 0836
e-mail: asiasales@zebra.com

Latin America

Zebra Technologies Corporation
Card Imaging Division
6175 NW 153rd St. #121
Miami Lakes, FL 33014
USA
Telephone: +1 305 558 3100
Fax: +1 305 558 8485
e-mail: latinsales@zebra.com